



优势

- 超高效率等级
- 多种尺寸规格
- 逐台检测H13效率等级
- 结构紧凑

应用	适用于送风/排风末端或安全箱体等扫描测试应用, 大流量高效过滤器
密封垫	无缝发泡聚氨酯
滤材	玻璃纤维
分隔物	热熔胶
最大终阻力	500 Pa
最高温度 (°C)	70°C
备注	阻燃等级: DIN 53438 Class F1



料号	类型	EN1822	尺寸 WxHxD (mm)	风量/初阻力 (m³/h/Pa)	重量 (kg)
1400507C	CED11-305x610x150-P0	E11	305x610x150	590/125	6
1400504C	CED11-610x610x150-P0	E11	610x610x150	1190/125	12
1400502C	CED11-914x610x150-P0	E11	914x610x150	1790/125	15
1400557C	CEX11-305x610x150-P0	E11	305x610x150	770/125	6
1400554C	CEX11-610x610x150-P0	E11	610x610x150	1560/125	12
1400552C	CEX11-914x610x150-P0	E11	914x610x150	2335/125	15
1400654C	CEG11-305x610x292-P0	E11	305x610x292	950/125	7,2
1400652C	CEG11-610x610x292-P0	E11	610x610x292	1900/125	12,5
1400651C	CEG11-762x610x292-P0	E11	762x610x292	2380/125	16
1400704C	CET11-305x610x292-P0	E11	305x610x292	1190/125	7,2
1400702C	CET11-610x610x292-P0	E11	610x610x292	2380/125	13
1400701C	CET11-762x610x292-P0	E11	762x610x292	2975/125	16,2
1400007C	CED13-305x610x150-P0-S	H13	305x610x150	645/250	6
1400004C	CED13-610x610x150-P0-S	H13	610x610x150	1305/250	12
1400002C	CED13-914x610x150-P0-S	H13	914x610x150	1958/250	15
1400057C	CEX13-305x610x150-P0	H13	305x610x150	773/250	6
1400054C	CEX13-610x610x150-P0-S	H13	610x610x150	1565/250	12
1400052C	CEX13-914x610x150-P0-S	H13	914x610x150	2348/250	15
1400154C	CEG13-305x610x292-P0-S	H13	305x610x292	893/250	7
1400152C	CEG13-610x610x292-P0-S	H13	610x610x292	1804/250	12,5
1400151C	CEG13-762x610x292-P0-S	H13	762x610x292	2251/250	16
1400204C	CET13-305x610x292-P0-S	H13	305x610x292	1230/250	7
1400202C	CET13-610x610x292-P0-S	H13	610x610x292	2485/250	12,5
1400201C	CET13-762x610x292-P0-S	H13	762x610x292	3100/250	16

可根据客户需求定制非标尺寸