



优势

- 锥形滤袋, 优化过滤面积
- 经济型
- 金属框架, 稳定牢固

应用	舒适型空调应用、预过滤器应用
外框	镀锌钢
滤材	复合纤维
尺寸	过滤器截面尺寸(EN15805)
最大风量	1,25 x 额定风量
最高温度 (°C)	70°C
最大相对湿度	90%
安装选项	提供前部和侧面可拆卸的外壳及框架



类型	EN779	ISO16890	尺寸 WxHxD (mm)	风量 (立方米/小时)	阻力 (Pa)	袋数	重量 (kg)	能耗	能耗等级	ePM1	ePM1min	ePM2,5	ePM2,5min	ePM10
A5	M5	ePM10 50%	592x592x600	3400	50	6	2,4	929	D	9	3	20	12	54
C5	M5	ePM10 50%	287x592x600	1700	50	3	1,5		D					
A5/520	M5	ePM10 50%	592x592x520	3400	55	6	2	940	D	9	3	20	12	54
B5/520	M5	ePM10 50%	490x592x520	2800	55	5	1,8		D					
C5/520	M5	ePM10 50%	287x592x520	1700	55	3	1,2		D					
B5	M5	ePM10 50%	490x592x600	2800	50	5	2,1		D					
A5/370	M5	ePM10 50%	592x592x370	3400	60	6	1,8	>1100	E	9	3	20	12	54
B5/370	M5	ePM10 50%	490x592x370	2800	60	5	1,6		E					
C5/370	M5	ePM10 50%	287x592x370	1700	60	3	1,2		E					
A6	M6	ePM10 70%	592x592x600	3400	60	6	2,4	>1300	E	30	8	40	18	71
B6	M6	ePM10 70%	490x592x600	2800	60	5	2,1		E					
C6	M6	ePM10 70%	287x592x600	1700	60	3	1,5		E					
A6/520	M6	ePM10 70%	592x592x520	3400	65	6	2	>1300	E	30	8	40	18	71
B6/520	M6	ePM10 70%	490x592x520	2800	65	5	1,8		E					
C6/520	M6	ePM10 70%	287x592x520	1700	65	3	1,2		E					
A6/370	M6	ePM10 70%	592x592x370	3400	85	6	1,8	>1300	E	30	8	40	18	71
B6/370	M6	ePM10 70%	490x592x370	2800	85	5	1,6		E					
C6/370	M6	ePM10 70%	287x592x370	1700	85	3	1,2		E					
A7	F7	ePM2,5 70%	592x592x600	3400	120	6	2,4	1937	D	57	41	71	60	90
B7	F7	ePM2,5 70%	490x592x600	2800	120	5	2,1		D					
C7	F7	ePM2,5 70%	287x592x600	1700	120	3	1,5		D					
A7/520	F7	ePM2,5 70%	592x592x520	3400	135	6	2	>2000	E	57	41	71	60	90
B7/520	F7	ePM2,5 70%	490x592x520	2800	135	5	1,8		E					
C7/520	F7	ePM2,5 70%	287x592x520	1700	135	3	1,2		E					
A7/370	F7	ePM2,5 70%	592x592x370	3400	185	6	1,8	>2000	E	57	41	71	60	90
B7/370	F7	ePM2,5 70%	490x592x370	2800	185	5	1,6		E					
C7/370	F7	ePM2,5 70%	287x592x370	1700	185	3	1,2		E					
UF7	F7	ePM2,5 70%	592x592x600	3400	110	8	2,6	1790	D	57	41	71	60	90
UH7	F7	ePM2,5 70%	287x592x600	1700	110	4	1,5		D					
UG7	F7	ePM2,5 70%	490x592x600	2800	110	6	2,4		D					
UF7/520	F7	ePM2,5 70%	592x592x520	3400	120	8	2,6	1971	D	57	41	71	60	90
UG7/520	F7	ePM2,5 70%	490x592x520	2800	120	6	2,4		D					
UH7/520	F7	ePM2,5 70%	287x592x520	1700	120	4	1,5		D					

类型	EN779	ISO16890	尺寸 WxHxD (mm)	风量(立方米/小时)	阻力 (Pa)	袋数	重量(kg)	能耗	能耗等级	ePM1	ePM1min	ePM2,5	ePM2,5min	ePM10
UF7/370	F7	ePM2,5 70%	592x592x370	3400	150	8	2,4	>2000	E	57	41	71	60	90
UG7/370	F7	ePM2,5 70%	490x592x370	2800	150	6	2,1		E					
UH7/370	F7	ePM2,5 70%	287x592x370	1700	150	4	1,5		E					
UF8	F8	ePM1 70%	592x592x600	3400	155	8	2,8	2458	E	70	60	80	70	90
UG8	F8	ePM1 70%	490x592x600	2800	155	6	2.6		E					
UH8	F8	ePM1 70%	287x592x600	1700	155	4	1.7		E					
UF8/520	F8	ePM1 70%	592x592x520	3400	170	8	2.7		E	70	60	80	70	90
UG8/520	F8	ePM1 70%	490x592x520	2800	170	6	2.5		E					
UH8/520	F8	ePM1 70%	287x592x520	1700	170	4	1.6		E					

能耗, 千瓦时/年: 根据Eurovent 4/21-2019指南计算

能效等级: 根据Eurovent RS 4/C/001-2019标准

可根据要求提供20毫米集气框

初阻力偏差±15%